

Hydraulic rotator motor

HPM
GROUP

Selection table

// MAX. AXIAL LOAD STATIC	// TORQUE	// UPPER CONNECTION Φ	// LOWER AXLE D & HOLE Φ	// LOWER FLANGE D X POS & BOLT HOLE Φ
10 kN	350-1000 Nm	25 mm	d39.5 D20 mm	$\square 100$ M16 mm
30 kN	1100-1350 Nm	30 mm	d49.5 D25 mm	$\square 140$ D17 mm
45 kN	1600-2500 Nm	35 mm	d59 D30 mm	d173x4 D17 mm
55 kN	2900-3400 Nm	45 mm	d59x50 D30 mm	d173x6 D17 mm
60 kN	>3400 Nm	50.8 mm	d68x56 D30 mm	d204x8 D17 mm
100 kN		52.2 mm	d69 D30 mm	d203x6 D21 mm
120 kN		56 mm	d78x64 D35 mm	- mm
160 kN			- mm	

// UPPER CONNECTION L

- <60 mm
- 60-75 mm
- 80-103 mm
- >136 mm



Hydraulic rotator motor

Replacement with Baltrotors/Ferrari International/Finn-Rotor/Formiko Hydraulics/
Black Bruin/Bakker Hydraulic Products BV/Thumm Oelhydraulische Antriebe GmbH/
AHydraulics/AVS Rotators ect...

Parts description

